

Vacuum Drying Oven



BOV-30V/BOV-50V



BOV-90V/BOV-215V



BOV-90VL/BOV-215VL

Features:

- * PID microprocessor temperature control with LED display.
- * Polished stainless steel inner chamber.
- * Vacuum degree is automatically controlled (for BOV-90V/BOV-215V/BOV-90VL/BOV-215VL)
- * Silicon rubber seal ring ensures the high vacuum degree in the chamber.
- * Tempered double-layer glass door ensures the operation safety.
- * The vacuum is controlled by microprocessor controller with digital display.(for BOV-90VL/BOV-215VL)
- * The working program has no circulation, no program control.(for BOV-90VL/BOV-215VL)
- * The vacuum pump is standard accessory(for BOV-90V/BOV-215V/ BOV-90VL/BOV-215VL)
- * Inert gas can be filled in the chamber. (Inert gas pressure is not higher than 0.1Mpa when filling in) (for BOV-90VL/BOV-215VL)

Technical Parameters:

Model	BOV-30V	BOV-50V	BOV-90V	BOV-215V	BOV-90VL	BOV-215VL
Capacity	23L	53L	91L	213L	91L	213L
Temp. Range	50~200°C	50~250°C	50~200°C			
Temp. Fluctuation	±1°C					
Vacuum Degree	<133Pa					
Vacuum Control	Manual control		Automatically; Include one vacuum meter		Automatically; Microprocessor controller with digital display	
Shelves No.	1 pc	2 pcs	2 pcs	3 pcs	2 pcs	3 pcs
Consumption	500W	1400W	1600W	2200W	1600W	2200W
Power Supply	AC220V±10%, 50/60Hz(Standard); AC110±10%, 60Hz(Optional)					
Internal Size(W*D*H) mm	296*300*270	416*370*346	450*450*450	556*600*640	450*450*450	556*600*640
External Size(W*D*H) mm	590*492*468	710*562*544	611*641*1398	721*794*1638	611*641*1398	721*794*1638
Package Size(W*D*H) mm	740*620*630	820*700*690	790*750*1570	900*850*1930	790*750*1570	900*850*1930
Gross Weight(kg)	50	106	155	195	155	195